

Categories		IN-CEILING SPEAKER WITHOUT BACKCAN				
Model Name		VC8N	VC6N		VC4N	
DME library file name		VC8N.cel	VC6N.cel	VC6N_sub.cel	VC4N.cel	VC4N_sub.cel
Drive Mode		Passive	Passive	Passive	Passive	Passive
Output Name		Full-range	Full-range	Full-range	Full-range	Full-range
Gain	(dB)	0.0	0.0	0.0	0.0	0.0
Delay	(ms)	none	none	none	none	none
Polarity		Normal	Normal	Normal	Normal	Normal
HPF	Freq (Hz)	40.0	40.0	100.0	40.0	100.0
	Slope (dB)	12	12	24	12	24
	Type	Butterworth	Butterworth	Butterworth	Butterworth	Butterworth
LPF	Freq (Hz)					
	Slope (dB)					
	Type					
PEQ1	Freq (Hz)	80.0	80.0	230	109.0	109.0
	Level (dB)	6.0	6.0	-5.5	4.0	4.0
	Type	Bell	Bell	Bell	Bell	Bell
	Q	2.0	2.8	4.2	2.8	2.8
	Bandwidth	0.714	0.513	0.343	0.513	0.513
PEQ2	Freq (Hz)	230	230	1,500	250	250
	Level (dB)	-3.0	-5.5	-4.0	-6.0	-6.0
	Type	Bell	Bell	Bell	Bell	Bell
	Q	4.2	4.2	1.8	4.2	4.2
	Bandwidth	0.343	0.343	0.792	0.343	0.343
PEQ3	Freq (Hz)	1,000	1,500	3,150	1,630	1,630
	Level (dB)	-2.5	-4.0	3.5	-2.5	-2.5
	Type	Bell	Bell	Bell	Bell	Bell
	Q	3.0	1.8	2.0	3.0	3.0
	Bandwidth	0.479	0.792	0.714	0.479	0.479
PEQ4	Freq (Hz)	4,100	3,150		6,000	6,000
	Level (dB)	-1.0	3.5		-3.5	-3.5
	Type	Bell	Bell		Bell	Bell
	Q	2.4	2.0		3.0	3.0
	Bandwidth	0.597	0.714		0.479	0.479
PEQ5	Freq (Hz)	11,200				
	Level (dB)	-3.0				
	Type	Bell				
	Q	4.2				
	Bandwidth	0.343				
PEQ6	Freq (Hz)					
	Level (dB)					
	Type					
	Q					
	Bandwidth					
Limiter	Threshold					
	Attack					
	Release					